

**EPIA PWB-M120 (Preliminary)**

<b>DC Input</b>	<b>Input</b>	<b>Minimum</b>	<b>Nominal</b>	<b>Maximum</b>		
	Voltage	11.4V~22.8V	12V~24V	12.6V~25.2V		
	Current	5.42A~10.84A				
<b>DC Output Voltage</b>	<b>Output</b>	<b>Minimum</b>	<b>Minimum</b>	<b>Maximum</b>	<b>Maximum Combined Power</b>  122.2W	
	+5V_SB	4.75V	5V	5.25V		
	+3.3V	3.14V	3.3V	3.47V		
	+5V	4.75V	5V	5.25V		
	+12V	11.4V	12V	12.6V		
	-12V	-13.2V	-12V	-10.8V		
	Power Good	4.75V	5V	5.25V		
<b>DC Output Current</b>	<b>+5V_SB</b>	<b>+3.3V</b>	<b>+5V</b>	<b>+12V</b>	<b>-12V</b>	<b>Power Good</b>
	2A	6A	6A	5A	200mA	0.1A
<b>Protection</b>	<ul style="list-style-type: none"> <li>- Output Voltage Protection (Over Voltage Protection) OVP</li> <li>- Output Current Protection (Output Short Protection)</li> <li>- Output Voltage Protection (Under Voltage Protection) UVP</li> </ul>					
<b>Operating Temperature</b>	0 ~ 50 ° C					
<b>Operating Humidity</b>	0% ~ 95% (relative humidity; non-condensing)					
<b>Form Factor</b>	<ul style="list-style-type: none"> <li>- 4 Layers</li> <li>- 15cm x 5cm</li> </ul>					

\* The specification is subject to change without prior notice.