

Mediant™ 8000 VoIP Media Gateway



- **IMS ready, carrier-grade, High-Density VoIP Media Gateway**
- **Cost-effective Media Gateway, scalable up to 16,000 protected VoIP channels**
- **Ready for all-IP networks using integrated IP-To-IP and transcoding applications**
- **Enables true convergence between multiple carrier networks on a single media gateway platform**
- **Provides high voice quality, supporting a wide range of low bit-rate to wideband high-definition voice coders**
- **Provides rich PSTN interfaces and signaling, supporting all industry standard control protocols**
- **Offers advanced security suite for enterprise and VoIP carrier networks, complying with U.S. Department of Defense security requirements**
- **Deployed globally at Tier 1, 2 and 3 service providers and large enterprise networks by leading OEMs and system integrators**

The **Mediant™ 8000** VoIP Media Gateway is a scalable, IMS-ready, standards-compliant, high channel density system for wireline, wireless, cable, broadband access and Fixed-Mobile-Convergence networks.

CARRIER-GRADE HIGH AVAILABILITY

The Mediant 8000 offers robust architecture meeting service providers' stringent requirements for high availability. This high availability architecture is based on cost-effective N+1 redundancy of the processing blades and load sharing of fans and power supplies.

MULTISERVICE MEDIA GATEWAY

The Mediant 8000 Media Gateway provides extensive support for regional PSTN interfaces, broad voice coder options, Signaling Gateway Interworking, control protocols and advanced security features, enabling multiservice deployment flexibility for a variety of customers (ILECs, IOCs, CLECs, MSOs, large Enterprises and contact centers).

The Mediant 8000 can be used for backhauling TDM over IP, part of class 4 & 5 TDM switch replacements, IP interconnection, IP service node, IP Centrex Applications and as a PacketCable gateway. In the wireless/cellular space, the Mediant 8000 is ideal for UMA and Femtocell applications. The Mediant 8000 allows Network Equipment Providers (NEPs) and Independent Software Vendors (ISVs) to immediately address opportunities for these services due to its advanced deployment flexibility.

HIGH LEVEL OF SCALABILITY

The Mediant 8000 is a modular platform which can scale up to 16,000 protected channels, allowing customers to begin with a low capacity entry point and later extend to a higher capacity by increasing the number of processing blade modules.

ALL-IP EVOLUTION

With the introduction of Next Generation networks, there is a growing demand for IP to IP transcoding in peering, access and Fixed-Mobile-Convergence scenarios. The Mediant 8000 has the flexibility to primarily be installed as a classic VoIP Media Gateway, and in parallel accommodate the growing demand of IP peering as PSTN interfaces are gradually being phased out.

TRUE NETWORK CONVERGENCE ON A SINGLE PLATFORM

The Mediant 8000 offers a high voice quality ranging from low-bit rate to wideband coders. This enables true network convergence between mobile/wireless networks and fixed line, cable and broadband networks on a single media gateway platform.

BROAD PSTN INTERFACES OPTIONS AND PROTOCOLS

The Mediant 8000 provides the flexibility to be globally deployed, interfacing with all popular PSTN interfaces, including E1, T1, J1, DS3 and OC3/STM1.

ADVANCED SECURITY SUITE

With the advent of VoIP, security has become a mandatory requirement. The Mediant 8000 addresses service providers and large enterprises security concerns, offering advanced security capabilities which include Interface Separation, SRTP for media, IPSec for control, OAM and TLS and PKI for SIP.



AudioCodes Voice Network Products for Wireline, Wireless, Cable and Converged Applications

Mediant™ 8000

SPECIFICATIONS

Capabilities	
Capacity	Up to 16,000 protected VoIP/GSM/UMTS channels
Voice Coders	High Definition Voice Coders: G.722, G.722.2 (Wide Band AMR), G.729.1 ((Wideband G.729) ,EVRC Wireline: G.711, G.722, G.723.1, G.726/7, G.729A/B, EG.711, MS GSM, iLBC GSM/UMTS: GSM-FR, GSM EFR, AMR, AMR-WB CDMA: EVRC, EVRC-B, QCELP 8k, QCELP 13k Cable: G.711, G.726/7, G.723.1, G.728, G.729E, G.729A/B, iLBC Independent dynamic vocoder selection per channel (within each group) Not all coders can be used simultaneously. Some coders will result in channel density degradation
Echo Cancellation	G.165 and G.168 compliant
Fax Support	Fax/Modem Detection Control, T.38 (IP) compliant Group 3 fax relay and fax bypass (automatic fallback to G.711) support
DTMF	Packet side or PSTN side detection and generation, RFC 2833 compliant
Voice Over Packet Capabilities	Call progress tones, VAD, CNG, Dynamic programmable jitter buffer, DTMF detection and generation, E911 CAS support
Signaling	
PSTN	ISDN PRI, SS7/MTP2/3, CAS, MFC-R2, MF-R1, V5.2 ²
SIGTRAN	<ul style="list-style-type: none"> ISDN-IUA/SCTP SS7- M2UA/SCTP, M3UA/SCTP SS7
IP Transport	IETF RFC 3550, RFC 3551 RTP/IP Transport, TCP, UDP CDMA: IETF RFC 2658 and RFC 3558 RTP/UDP/IP UMTS: Nb IP User Plane and IPBCP over Mc per 3GPP
Media Gateway Control Protocols	MGCP (RFC 3435), TGCP, MEGACO (H.248, RFC 3015), SIP (RFC 3261) 3GPP: CS Mc - TS 29.232, IMS Mn - TS 29.332
Security	<ul style="list-style-type: none"> S RTP, Public Key Infrastructure Certificate for TLS IPSec (ESP) with IKE pre-shared key for secure Management with EMS/NMS/OSS and Control with MGC AES - 128 (Rijndael) cipher algorithm, in CBC mode for Media Security (RTP/RTCP) for packet cable SSH Protocol Version 2 for secure Telnet and SFTP Server transfers Firewall - for controlled IP access to Media Gateway Blades
Maintenance	
Management	Element Management System, SNMP v2 over IPSEC/SNMP v3, Command Line Interface (CLI)
Maintainability	All shelf modules are hot swappable, including boards, power supplies, fans
Redundancy Scheme	System Controller and Ethernet Switch blades: 1+1 Power supplies: N+1 Load Shared Media Gateway blades (including PSTN interfaces): N+1 Optical Interfaces (PSTN): 1+1, APS protected
Hardware Specifications	
Interfaces	PSTN: Up to 8 x OC-3/STM-1 Optical ports, each 1+1 APS protected, or up to 24 x T3 (DS-3) Copper Coax ports or up to 252 E1/T1/J1 spans IP: Dual Redundant 100/1000 BASE-T (aggregated) Ethernet ports, with Multi-VLAN Interfaces support (OAM, Control, Media) Clock Synchronization: BITS/SETS (GR-1244 Stratum-3 and G.813 compliant), line synchronization (via STM-1/OC-3 link or DS1 trunk)
Enclosure	21-slot, 12U cPCI chassis
Dimensions (HxWxD)	533 mm x 483 mm x 480 mm (21 x 19 x 18.9 inches)
Weight	Approx 60 lbs. (27 kgs.), unloaded Approx. 88 lbs. (40 kgs.), fully loaded
Mounting	Per EIA Standard RS-310-C in 19-inch rack
Midplane	<ul style="list-style-type: none"> PICMG 2.16 cPCI Packet Switching Backplane (cPSB) PICMG 2.1 cPCI hot swap specification PICMG 2.0 cPCI specification
Power	-48 V DC Dual Feed, with 3 DC Power modules
Cooling	Replaceable fan trays & filters
Regulatory Compliance	
Telecommunication Standards ³	FCC part 68 TBR4 and TBR13
Safety and EMC Standards	<ul style="list-style-type: none"> UL60950 • FCC part 15 Class A CE Mark (EN55022 Class A, EN60950, EN55024, EN300 386)
Environmental ³	NEBS Level 3: GR-63-Core, GR-1089-Core, Type 1 & 3, ETS300 019

ABOUT AUDIOCODES

AudioCodes Ltd. (NasdaqGS: AUDC) provides innovative, reliable and cost-effective Voice over IP (VoIP) technology, Voice Network Products, and Value Added Applications to Service Providers, Enterprises, OEMs, Network Equipment Providers and System Integrators worldwide. AudioCodes provides a diverse range of flexible, comprehensive media gateway, and media processing enabling technologies based on VoIPerfect(tm) – AudioCodes' underlying, best-of-breed, core media architecture. The company is a market leader in VoIP equipment, focused on VoIP Media Gateway, Media Server, Session Border Controllers (SBC), Security Gateways and Value Added Application network products. AudioCodes has deployed tens of millions of media gateway and media server channels globally over the past ten years and is a key player in the emerging best-of-breed, IMS based, VoIP market. The Company is a VoIP technology leader focused on quality and interoperability, with a proven track record in product and network interoperability with industry leaders in the Service Provider and Enterprise space. AudioCodes Voice Network Products feature media gateway and media server platforms for packet-based applications in the converged, wireline, wireless, broadband access, cable, enhanced voice services, video, and Enterprise IP Telephony markets. AudioCodes' headquarters and R&D are located in Israel with an additional R&D facility in the U.S. Other AudioCodes' offices are located in Europe, India, the Far East, and Latin America.

International Headquarters

1 Hayarden Street,
Airport City
Lod 70151, Israel
Tel: +972-3-976-4000
Fax: +972-3-976-4040

AudioCodes Inc.

27 World's Fair Drive,
Somerset, NJ 08873
Tel:+1-732-469-0880
Fax:+1-732-496-2298

Contact us: www.audiocodes.com/info
Website: www.audiocodes.com

©2009 AudioCodes Ltd. All rights reserved. AudioCodes, AC, AudioCoded, Ardito, CTI2, CTI², CTI Squared, HD VoIP, InTouch, IPmedia, Mediant, MediaPack, NetCoder, Netrake, Nuera, Open Solutions Network, OSN, Stretto, TrunkPack, VoicePacketizer, VoIPerfect, VoIPerfectHD, What's Inside Matters, Your Gateway To VoIP and 3GX are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners.

Ref. LTRM-40006 V.5 03/09