

TP-260 8 E1/T1 PCI VoIP Communication Board



- Complete media gateway on a module
- Low to high channel density
- Concurrent toll quality voice and fax support
- Media gateway on a blade mode
- Wide range of PSTN signaling protocols
- Fast time-to-market
- Flexible and easy migration to VoIP networks
- Extensive VoIP experience

The **TP-260** PCI VoIP communication board, based on AudioCodes' TPM-1100 PMC Modules, is an ideal solution for trunking gateways to the PSTN and integrated gateways for IP-PBXs and all-in-one communication servers. The TP-260 provides 256 ports for voice, fax or data implementing VoIP media gateway applications.

DELIVER FEATURE-RICH SOLUTIONS

The TP-260 supports a broad selection of voice processing related algorithms, including G.711, G.723.1 and G.729AB Vocoders, G.168-compliant echo cancellation, T.38 Real-time Fax over IP, as well as a wide selection of In-band and Out-band tone detection and generation. The TP-260 wide selection of TDM interfaces allows easy integration with other third party CTI boards. The E1/T1/J1 PSTN interface and wide range of supported telephony protocols provides TP-260 users a higher level of integration, saving backplane slot space, enabling higher density gateway platforms while reducing the costs per channel.

COMPLY WITH INDUSTRY STANDARDS

The TP-260 board complies with industry standard network control protocols including MGCP, MEGACO (H.248) as well as AudioCodes' proprietary TPNC. These allow for the implementation of a distributed gateway architecture that separates call-processing functions from media streaming functions, resulting in better redundancy, scalability and higher system availability.

PROTECT CUSTOMER INVESTMENT

The TP-260 is based on the VoIPerfect™ architecture, AudioCodes' underlying, best-of-breed, core media gateway technology for all of its products. The TP-260 supports AudioCodes' API, which enables software download, provisioning and control. It was designed to maintain essential API backward compatibility in order to protect customers' investment in the development of products based on former generations.

ENABLE FAST & EASY INTEGRATION

Enabling accelerated design cycles with low to high density and reduced costs, the TP-260 is an ideal building block for scalable, reliable VoIP solutions. With the TP-260's comprehensive feature set, customers can quickly design a wide range of solutions for smooth migration to VoIP networks.

TP-260 FEATURES

- 256 independent voice/fax/data ports
- VoIP packet streaming (RTP/RTCP)
- Standard control: MGCP (RFC 2705), MEGACO (H.248)
- Real-time Fax over IP/T.38
- On-board announcement support towards PSTN/TDM and IP
- Tone detection and generation (MF, DTMF, RFC 2833)
- PSTN signaling: CAS, ISDN PRI, and SS7
- SIGTRAN IUA, M2UA, M3UA over SCTP
- Media Gateway on a blade mode
- MVIP SCbus and H.100 TDM interfaces
- Management interfaces: SNMP, Web server
- On-board 10/100Base-T Network interface
- Optional universal PCI version

AudioCodes Enabling Technology Products

TP-260

SPECIFICATIONS

Software Specifications

Capacity	32, 64, 128, 256 independent digital voice, fax and data ports
Voice Compression	G.711, G.723.1, G.729A/B, G.726/G.727, NetCoder® MS-GSM, GSM-FR Additional coders supported – contact AudioCodes for further information
Echo Cancellation	G.168 compliant 32, 64 msec echo tail 128 msec tail available with reduced channel capacity
Fax Relay	Real-time fax over IP/T.38 compliant, automatic fallback to G.711 and VBD for up to super G-3 fax machines
ASR-3 rd party	Host-based architecture – media system PCI
Recognition Engines	Distributed Architecture - Media Stream over VoIP RTP
In-band/Out-band Signaling	Packet side or PSTN side, DTMF and tone detection and generation, CAS Relay, RFC 2883
IVR Support	On-board announcement storage – 10 Mb: 20 minutes of G.711, 200 minutes of G.723
VoIP Standards Compliance	RTP/RTCP per RFC 3550/3551 DTMF over RTP per RFC 2833
Control Protocols	Media Gateway on a blade mode: Controlled by either MGCP or MEGACO PCI used for power only AudioCodes' proprietary VoIP API Library over IP (TPNCP) or PCI
Management Interfaces	• SNMP V2c: Standard MIB-2, RTP MIB, DS1 MIB, AudioCodes proprietary MIB • Embedded Web Server
Operating System	• Windows™ 2000, XP, 2003 • Linux™ • Solaris™ on Sparc™/Intel™

Signaling

PSTN	CAS	T1 robbed bit, MFC/R2 numerous country variants
	CCS	ISDN PRI: numerous country variants including ETSI EURO ISDN, ANSI NI2, DMS, 5ESS, Japan INS1500
	SS7	MTP2 and MTP3 link termination
SIGTRAN		M2UA and M3UA and IUA over SCTP per RFC 3057/2960

Hardware Specifications

Ethernet	10/100 BASE-T
Physical Interfaces	Form factor - Full length PCI board TDM Interfaces - MVIP, SCbus or H.100 Telephony – 120 Ohm – RJ48C connectors Ethernet – RJ-45 Universal PCI 5 V/3.3 V signaling PCI bus – 32/64 bit, 33/66 MHz
Power	3.6A at 5 V with quad E1/T1 interface

APPLICATIONS

- Next Generation Switches
- VoIP Access Gateways
- Trunking Gateways
- IP-IVR
- IP-PBXs
- Enterprise Gateways

ABOUT AUDIOCODES

AudioCodes Ltd. (NASDAQ: AUDC) enables the new voice infrastructure by providing innovative, reliable and cost-effective Voice over Packet technology and Voice Network products to OEMs, network equipment providers and system integrators. AudioCodes provides its customers and partners with a diverse range of flexible, comprehensive media gateway and media processing technologies, based on VoIPerfect™ – AudioCodes' underlying, best-of-breed, core media gateway architecture. The company is a market leader in voice compression technology and is a key originator of the ITU G.723.1 standard for the emerging Voice over IP market. AudioCodes voice network products feature media gateway and media server platforms for packet-based applications in the converged, wireline, wireless, broadband access, and enhanced voice services markets. AudioCodes enabling technology products include VoIP and CTI communication boards, VoIP media gateway processors and modules, and CPE devices. AudioCodes' headquarters and R&D facilities are located in Israel with an R&D extension in the U.S. Other AudioCodes' offices are located in Europe, the Far East, and Latin America.

International Headquarters

1 Hayarden Street, Airport City
Lod, Israel 70151
Tel: +972-3-976-4000
Fax: +972-3-976-4040

US Headquarters

2099 Gateway Place, Suite 500
San Jose, CA 95110
Tel: +1-408-441-1175
Fax: +1-408-451-9520

info@audiocodes.com
www.audiocodes.com

© 2005 AudioCodes Ltd. All rights reserved. AC, Ardito, AudioCodes, AudioCodes logo, AudioCoded, IPmedia, Mediant, MediaPack, MP-MLQ, NetCoder, Stretto, TrunkPack, VoicePacketizer and VoIPerfect are trademarks or registered trademarks of AudioCodes Ltd. All other marks are the property of their respective owners. The information and specifications in this document and the product(s) are subject to change without notice.

Ref # LTRT-00257 08/05 V.7

